

**RCD/MCB combination, 40 A, 30 mA, MCB trip characteristic: C, 1p+N,  
RCD trip characteristic: AC**

**Part no. FRBMM-C40/1N/003-G  
170629**

Similar to illustration

<b>General specifications</b>		
Product name		Eaton Moeller series xEffect - FRBm6/M RCBO - residual-current circuit breaker with overcurrent protection
Part no.		FRBMM-C40/1N/003-G
EAN		4015081672134
Product Length/Depth		80 millimetre
Product height		75 millimetre
Product width		35 millimetre
Product weight		0.215 kilogram
Compliances		CE Marked RoHS conform
Certifications		EN45545-2 CE IEC 61373
Product Tradename		xEffect - FRBm6/M
Product Type		RCBO - Residual-current circuit breaker with overcurrent protection
Product Sub Type		None
<b>Delivery program</b>		
Application		Switchgear for industrial and advanced commercial applications
Product range		FRBmM
Basic function		Combined RCD/MCB devices
Number of poles		Single-pole + N
Number of poles (protected)		1
Number of poles (total)		2
Tripping characteristic		C
Release characteristic		C
Amperage Rating		40 A
Rated current		40 A
Fault current rating		0.03 A
Sensitivity type		AC current sensitive
Type		RCBO
<b>Technical Data - Electrical</b>		
Voltage type		AC
Voltage rating		240 V - 240 V
Rated operational voltage (Ue) - max		240 V
Rated insulation voltage (Ui)		500 V
Rated impulse withstand voltage (Uimp)		4 kV
Rated fault currents of product range		10, 30, 100, 300 MilliAmpere
Impulse withstand current		Surge-proof, 3 kA
Frequency rating		50 Hz
Leakage current type		AC
Rated switching capacity		10 kA
Rated switching capacity (IEC/EN 61009)		10 kA
Rated short-circuit breaking capacity (EN 60947-2)		10 kA
Rated short-circuit breaking capacity (EN 61009)		10 kA
Rated short-circuit breaking capacity (EN 61009-1)		10 kA
Rated short-circuit breaking capacity (IEC 60947-2)		10 kA

Surge current capacity			3 kA
Disconnection characteristic			Short-time delayed
Tripping			Short time-delayed
Pollution degree			2
<b>Technical Data - Mechanical</b>			
Width in number of modular spacings			2
Built-in depth			75.5 mm
Degree of protection			IP20
Connectable conductor cross section (solid-core) - min			1 mm <sup>2</sup>
Connectable conductor cross section (solid-core) - max			25 mm <sup>2</sup>
Connectable conductor cross section (multi-wired) - min			1 mm <sup>2</sup>
Connectable conductor cross section (multi-wired) - max			25 mm <sup>2</sup>
<b>Design verification as per IEC/EN 61439 - technical data</b>			
Rated operational current for specified heat dissipation (In)			40 A
Heat dissipation per pole, current-dependent			0 W
Equipment heat dissipation, current-dependent			8.2 W
Static heat dissipation, non-current-dependent			0 W
Heat dissipation capacity			0 W
Ambient operating temperature - max			40 °C
Ambient operating temperature - min			-25 °C
<b>Design verification as per IEC/EN 61439</b>			
10.2.2 Corrosion resistance			Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures			Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects			Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation			Meets the product standard's requirements.
10.2.5 Lifting			Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact			Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions			Meets the product standard's requirements.
10.3 Degree of protection of assemblies			Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances			Meets the product standard's requirements.
10.6 Incorporation of switching devices and components			Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections			Is the panel builder's responsibility.
10.8 Connections for external conductors			Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength			Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage			Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material			Is the panel builder's responsibility.
10.10 Temperature rise			The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function			The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
<b>Additional information</b>			
Current limiting class			3
Features			Concurrently switching N-neutral Anti- nuisance tripping version

## Technical data ETIM 9.0

Circuit breakers and fuses (EG000020) / Earth leakage circuit breaker (EC000905)			
Electric engineering, automation, process control engineering / Electrical installation, device / Residual current protection system / MCB/RCCB combination (ecl@ss13-27-14-22-07 [AFZ810020])			
Number of poles (total)			2
Number of protected poles			1
Rated voltage		V	240
Rated insulation voltage Ui		V	500
Rated impulse withstand voltage Uimp		kV	4

Rated current	A	40
Rated fault current	A	0.03
Leakage current type		AC
Current limiting class		3
Power loss	W	
Rated short-circuit breaking capacity according to EN 61009	kA	10
Rated short-circuit breaking capacity according to IEC 60947-2	kA	10
Rated short-circuit breaking capacity I <sub>cn</sub> according to EN 61009-1	kA	10
Disconnection characteristic		Short-time delayed
Surge current capacity	kA	3
Voltage type		AC
Frequency		50 Hz
Release characteristic		C
Concurrently switching neutral conductor		Yes
With interlocking device		No
Over voltage category		3
Pollution degree		2
Ambient temperature during operating	°C	-25 - 40
Width in number of modular spacings		2
Built-in depth	mm	75.5
Flush-mounted installation		No
Anti- nuisance tripping version		Yes
Degree of protection (IP)		IP20
Connectable conductor cross section solid-core	mm <sup>2</sup>	1 - 25
Connectable conductor cross section multi-wired	mm <sup>2</sup>	1 - 25